



**ENTRUST**



# EM2 Direct-to-Card Printer

Efficient, affordable dual-sided printing

## OVERVIEW

The Entrust EM2 Direct-to-Card Printer is all about value and versatility. With dual-sided printing, secure card encoding capabilities, and USB and ethernet connectivity, it's the perfect budget-friendly printer for a variety of applications such as:

- Corporate IDs
- Student IDs
- Retail gift and loyalty cards
- Membership ID cards
- Transportation cards

## KEY FEATURES AND BENEFITS

### Small footprint

Allows users to work effectively in any location or workstation size.

### Efficient

Print up to 880 single-sided monochrome cards per hour; 225 full-color single-sided cards per hour.

### Versatile

- Single- or dual-sided printing
- USB and ethernet connectivity
- Contact and contactless smart card encoding

### Affordable

The EM2 card printer and its supplies are competitively priced to fit modest budgets.

### Secure card option

Smart card and magnetic stripe encoding options allow you to create secure ID cards to give authorized users secure access to facilities, networks, and other privileges.

**LEARN MORE AT [ENTRUST.COM](https://www.entrust.com)**



# EM2 Direct-to-Card Printer

## TECHNICAL SPECIFICATIONS

### Standard Features and Supplies

Print technology	Dye sublimation
Print capabilities	Single- or dual-sided
Print resolution	300 dots per inch
Print speed	Single-sided full-color (YMCKT): up to 225 cards per hour (cph) Single-sided monochrome: up to 880 cph
Card capacity	Input hopper: 125 cards Output hopper: 25 cards Reject hopper: 10 cards
Card sizes	Thickness: 0.01 in. – 0.04 in. (0.25 mm – 1.016 mm) Dimension: CR-80, CR-79
Operating environment	60°F – 95°F (15°C – 35°C)
Physical dimensions	L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm
Weight	Single-sided printing: 11.3 lbs. (5.13 kg)
Connectivity	USB and Ethernet
Warranty	24 months

### Operational Features and Supplies\*

Magnetic stripe encoding	ISOA/IAT
Smart card encoding	Loosely coupled: <ul style="list-style-type: none"> <li>• Contact: ISO7816 T=0 (T=1) (dual-sided only)</li> <li>• Contactless: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE® DESFire® EV1/ EV2, HID Prox, iClass, iClass SE, iClass Seos, dual-sided only: Felica</li> </ul>
Color ribbons**	YMCKT            250/500 images ymcKT            650 images YMCKT-KT:      350 images ymcKT-KT:      435 images
Monochrome ribbons***	Black            1,500 images White            1,500 images Additional monochrome options available

\* All supply yields are estimates and vary based on use conditions.

\*\* Color Panel Ribbons state the absolute maximum yield possible.

\*\*\* Monochrome Ribbons state the maximum yield based on full card print coverage. Entrust ribbon conservation technology enables monochrome ribbons to increase yield based on actual images printed for each card.

Learn more at  
**entrust.com**



Entrust and the Hexagon logo are trademarks, registered trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer.  
© 2020 Entrust Corporation. All rights reserved. DP21Q3-acc-em2-printer-ds

U.S. Toll-Free Phone: 888 690 2424  
International Phone: +1 952 933 1223  
**info@entrust.com**